



LMP

Line Marking Paint

Applications

Ultracrete Line Marking Paint (LMP) is a solvent based marking paint, ideal as an effective and quick method for line or spot marking in road and pot hole repairs, car parks, warehouses, building sites, sports areas, excavation sites, mining, turf marking and landscape sites. The semi-permanent formula is effective for at least 3 months after application under normal wear conditions.

Technical

Ultracrete LMP is supplied in 750ml aerosol cans and is available in White (MP1), Yellow (MP2), Red (MP3) and Blue (MP4). The colour of the plastic cap on the aerosol tin denotes the colour of the product. When placing an order, please quote the code numbers above to indicate the colour required.

Application

Ensure the surface to be marked is dry and free from dust. Shake the aerosol tin well for 2-3 minutes. Invert can and spray in even strokes from a distance of 175mm-250mm (7"-10") from the surface to be marked. After use turn can upright and spray for 1-2 seconds to clear nozzle. Product will cover almost any surface including epoxy resin coatings. Note: Please take care when clearing the nozzle and painting; do not paint in windy conditions.

Health & Safety

This product should not come into contact with skin or eyes. Avoid inhalation of fumes and ensure that work is carried out in well-ventilated conditions. Protective clothing, gloves and respiratory equipment should be worn if not well ventilated. The product can be removed from the skin by using soap and water, seek medical attention if discomfort continues. Repeat exposure may cause skin dryness or cracking. If swallowed, do not induce vomiting, rinse mouth thoroughly with water if conscious and seek medical attention if discomfort continues. Note: This product is extremely flammable. The propellant in this can may explode if exposed to excessive heat or naked flame. For a full updated Material Safety Data Sheet please visit www.instarmac.co.uk

Disposal

Pressurised container. Do not pierce or burn, even after use.



Features & Benefits

- Economical
- Contains no chlorinate solvents
- Bio-degradable in dissipation



Related Products

- Ultracrete Instaband** Skid Resistant Overbanding Tape
- Ultracrete Instaline** Thermoplastic Road Marking
- Ultracrete Instagrip** Anti-Skid Patch Repair

continued



LMP

Line Marking Paint

Product Details

Unit/Packaging	750ml aerosol can, 12 per box
Storage	Aerosol cans must NOT be exposed to direct sunlight or temperatures above 50°C. Store in a cool well-ventilated place
Shelf Life	Shelf life in correct conditions for sealed packaging is 6 months. In cold weather conditions, storing overnight at room temperature will assist application
Coverage	Approximately, 350 linear metres per can, dependant on thickness applied
Colours and Colour Codes	<input type="checkbox"/> White MP1 <input type="checkbox"/> Yellow MP2 <input type="checkbox"/> Red MP3 <input type="checkbox"/> Blue MP4

Contact Us

Instarmac® Group plc, Birch Coppice Business Park, Danny Morson Way, Dordon, Tamworth, Staffordshire, B78 1SE, United Kingdom

Tel: +44 (0) 1827 872244 Fax: +44 (0) 1827 874466

Email: email@instarmac.co.uk Order: orders@instarmac.co.uk Website: www.instarmac.co.uk

Ultracrete products are guaranteed against defective materials and manufacture, and will be replaced or money refunded if the goods do not comply with our promotional literature. We cannot however accept any liability arising from the application or use of our products because we have no direct or continuous control over where and how our products are used. All products are sold subject to our conditions of sale, copies of which may be obtained on request.

An **INSTARMAC®** Brand